



**CYCLONE**

TURBO PRESSURE  
COMPENSATING DRIPPER



**STORM**

TURBO NON-PRESSURE  
COMPENSATING 3 PIECE DRIPPER



**HURRICANE**

NON-PRESSURE  
COMPENSATING DRIPPER

## Non-Pressure Compensating and Pressure Compensating Online Dripper


## Salient Features

- ◆ Wide and deep turbulent labyrinth designed to mitigate clogging.
- ◆ Self-cleaning labyrinth that removes debris, enhancing longevity for sustained performance throughout multiple seasons.
- ◆ Resistant to UV rays and chemicals, ensuring an extended and resilient operational life.
- ◆ PC drippers provide efficient discharge in steep topography and feature a drainage prevention mechanism to minimize the refill effect and biological blockage.
- ◆ Precise water delivery with CV of less than 2.5% for optimal efficiency.
- ◆ Available with a wide range of distances to cater to multiple applications.


## Application



Vineyards



Trees and  
Orchards



Greenhouse



Nursery



Hydroponics

# ONLINE DRIPPER


**PARAGON**  
— Since 1994 —

CYCLONE	
BLUE	0.53 GPH
BLACK	1.05 GPH
RED	2.00 GPH


STORM	
BLACK	0.53 GPH
GREEN	1.05 GPH
RED	2.00 GPH
BLUE	3.70 GPH

HURRICANE	
GREEN	4.24 GPH
RED	2.00 GPH

Dripper	Nominal Flow Rate LPH (GPH)	Pressure (LPH VS KG/CM2)						Pressure (GPH VS PSI)					
		0.5	1	1.5	2	2.4	2.8	7.111	14.223	21.335	28.446	34.136	39.825
CYCLONE (PC)	2 (0.52)	2.19	2.00	2.00	2.00	2.00	2.00	0.580	0.530	0.530	0.530	0.530	0.530
	4 (1.05)	4.23	3.97	3.97	4.01	4.01	4.01	1.120	1.050	1.050	1.060	1.060	1.060
	7.57 (2)	7.64	7.57	7.57	7.60	7.64	7.60	2.020	2.000	2.000	2.010	2.020	2.010
STORM (NPC)	2 (0.53)	1.55	2.04	2.49	3.02	-	-	0.410	0.540	0.660	0.800	-	-
	4 (1.05)	3.10	4.05	5.03	5.64	-	-	0.820	1.070	1.330	1.490	-	-
	7.57 (2)	5.82	7.94	9.61	10.78	-	-	1.540	2.100	2.540	2.850	-	-
HURRICANE (NPC)	14 (3.7)	9.53	14.04	16.46	17.56	-	-	2.520	3.710	4.350	4.640	-	-
	7.57 (2)	5.60	7.57	9.38	7.57	-	-	1.480	2.050	2.480	2.760	-	-
HURRICANE (NPC)	16.05 (4.24)	16.05	15.97	19.60	21.34	-	-	2.980	4.220	5.180	5.640	-	-



MAX OPERATING PRESSURE 40 PSI




120/125 Mesh/Micron FILTRATION REQUIRED



CYCLONE BARBED OUTLET COMPATIBLE WITH 3MM, 5 MM AND 1/8 TUBE

## Componets



**Polyethylene Tubing**

Manufactured using cutting-edge machinery for extended life.



**Micro Tubing**

Superior quality micro tubing




**Punch**

Custom made punch for precise and leakproof fitting



**Goof Plug**

Barbed plugs to plug holes



2371 Grand Ave Unit 2469 Long Beach, CA, USA 90809  
 contactus@paragonirrigation.com www.paragonirrigation.com